

## Systevo DECT central unit




**Part-No.: 790D150**

Central unit as basic housing for the telecommunication system according to the DECT/GAP standard for upgrading a telephone system with analogue extension participants and/or VoIP participants. The modular system upgrade of the central unit in accordance with the customer requirements with a CPU card and various plug-in cards for the administration of the DECT base stations and extension users (a/b and VoIP/SIP). In a Systevo DECT system, up to 250 base stations and 500 DECT telephones can be used. The assembly takes place in a 19" installation cabinet or alternatively in connection with the optional wall bracket.

**Features:**

- 1 central casing with Backplane
- 1 Power supply unit for the supply of the plug-in cards
- Max. installation of 1 CPU-card and 8 further plug-in cards
- For more than 4 "Base station control units", a separate power pack is necessary
- Redundancy operation possible with the 2nd power pack

Frequency range	1880 MHz ... 1900 MHz
Ambient temperature	0 °C ... 40 °C
Air humidity	< 20 %
Mounting	for installation in rack housing
Weight	approx. 5,34 kg without power supply (max. 12 kg with power supply units)
Dimensions	W: 422 mm H: 177 mm D: 330 mm

 Systevo DECT central unit System documentation System software for set-up and configuration

**Accessories:**

790D001	Connection cable 5 m PC
790D155	Alternatively 790D156 CPU card for central unit 19"
790D160	Control unit base station (8)
790D170	Alternatively 790D175 PABX interface card (8 a/b or 16 a/b)
790D177	PABX interface card VoIP/SIP
790D180	Power supply unit for central unit 19"
790D185	Wall bracket for central unit 19"