

## DECT-Telephone Series D5, Alarm



### Part-No.: 790D520

Like item 790D500, however, in addition, with an alarm button and extended memory for up to 20 text messages (> 150 characters). Automatic selection when pressing the alarm button of a preprogrammed phone number. Prepared for the display of messages in different colors as well as with special symbols (planning in future firmware of the central processing unit, functional support of the call system necessary).

Frequency range	1880 MHz ... 1900 MHz
Screen diagonal	4,5 cm
Weight	approx. 0,14 kg (incl.battery)
Dimensions	W: 53 mm H: 152 mm D: 27 mm

### Features:

- DECT telephone incl. battery
- Impact-resistant housing
- Headphone port
- Auxiliary loudspeaker
- 7-line color display
- Keypad and control keys
- Memory for 10 text messages (32 characters each)
- Address book (200 entries with 1000 numbers)
- Call list
- 13 menu languages
- Vibration device
- Different call signals
- Alarm button
- Certifications: TBR6(DECT RF), TBR22(GAP), EMC ETS300329, CE



The service life of a rechargeable battery depends on how often the battery has been charged (max. approx. 500 charging cycles). With 2 charges per day, this corresponds to approx. 12 months. In order to enable the maximum service life of the rechargeable battery, the charging process must always be fully completed. The charging process should only be started if the battery display is nearly empty (approx. 20 %). If the standby time becomes too short, the rechargeable battery should be replaced. The DECT terminal device cannot be operated on a "Clino Call DECT central unit" (installations before 2012). Contact our sales representative to work out a suitable solution for you.

### Accessories:

790D501	Battery for DECT telephone series D5
790D503	Leather case for DECT telephone series D5
790D510	Charging cradle for DECT telephone series D5