

Hydrogen Sulfide

Sensoric H2S 2E 50 S



Product Data Sheet

Sensoric H2S 2E 50 S

FEATURES

Amperometric 2 electrode sensor cell
fast response
high reliability
high selectivity

TYPICAL APPLICATIONS

TLV-monitoring, leakage detection
portable applications
Oil & Petrochemical industry, water treatment plants

PART NUMBER INFORMATION

MINI	0141-124-30009
SENSORIC CLASSIC	0141-124-30069
CTL4 series adaptation	0141-124-30049
CTL 7 series adaptation	0141-124-30079

Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.



Product Data Sheet

Sensoric H2S 2E 50 S

TECHNICAL SPECIFICATIONS

Measuring Range	0–50 ppm
Sensitivity Range	380 nA/ppm \pm 80 nA/ ppm
Zero Current at 20°C	< \pm 200 nA
Resolution at 20°C	< 0.7 ppm
Bias Potential	not required
Linearity	< 5% full scale
Response Time at 20°C	
t50	< 15 s calculated from 2 min. exposure time
t90	< 30 s calculated from 2 min. exposure time
Long Term Sensitivity Drift	< 10% per 6 months
Operation Conditions	
Temperature Range	-20°C to +40°C
Humidity Range	15–90% r.H., non-condensing
Effect of Humidity	an abrupt change of r. H. will cause a short term drift in zero reading of <1 ppm
Sensor Life Expectancy	> 48 months
Warranty	24 months


Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.



Product Data Sheet

Sensoric H2S 2E 50 S

OUTPUT vs. TEMPERATURE:




Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

Sensoric H2S 2E 50 S

ZERO READING vs. TEMPERATURE:



Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

Product Data Sheet

Sensoric H2S 2E 50 S

CROSS SENSITIVITIES AT 20 °C

Gas	Concentration	Reading [ppm]
Carbon Monoxide	100 ppm	<1
Chlorine	1 ppm	<±1
Nitrogen Dioxide	10 ppm	- 2
Sulfur Dioxide	20 ppm	3
Hydrogen	10000 ppm	<10
Isopropanol	200 ppm	0
Methane	2.2 %	0
Nitric Oxide	100 ppm	<±1

Notes:

1. Interference factors may differ from sensor to sensor and with life time. It is not advisable to calibrate with interference gases.
2. This table does not claim to be complete. The sensor might also be sensitive to other gases.

Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.



Product Data Sheet

Safety Note

This sensor is designed to be used in safety critical applications. To ensure that the sensor and/or instrument in which it is used, are operating properly, it is a requirement that the function of the device is confirmed by exposure to target gas (bump check) before each use of the sensor and/or instrument. Failure to carry out such tests may jeopardize the safety of people and property.

Attention

Use of the Sensoric range sensors requires complete understanding of the instructions. Before using Sensoric range sensors please carefully read 'Application Notes' which can be found at www.citytech.com under the heading 'Support' -> 'Application Notes' -> 'Sensoric'

Product Safety Data Sheets (PSDS) can be obtained at www.citytech.com under the heading 'Support' -> 'Product Safety Datasheets'

For further assistance on sensor selection and use, please contact a member of the Technical Sales team.

Sensoric deems the data contained herein as factual, and the opinions expressed are those of qualified experts based on the results of tests conducted. The above data can not be used as a warranty provision or representation for which Sensoric assumes legal responsibility. The data are offered solely for consideration, investigation and verification. Any use of this information is subject to federal, state and local laws and regulations.

