

MICRO SWITCH BASIC SWITCH SEALED SWITCH COMPARISON

Water-tight. Dust-tight. Miniature and subminiature switches. Sealed to IP67.
Compact size with industrial-grade performance.

SERIES	V15W2	V15W	ZD	ZW	HD	HD1
Type, Market	zone 2, hazardous locations	sealed, high current capacity	standard, sealed	standard, sealed	standard, sealed	standard, sealed
Sealing	IP67 equivalent	IP67 (prewired)	IP67 (prewired)	IP67 (prewired)	IP67 (prewired)	IP67 (prewired)
Amp rating (A)	5	0.1, 5, 6, 10	0.1, 3	0.1, 6	0.3 to 3	0.1
Voltage	125 Vac, 250 Vac	125 Vac, 250 Vac, 30 Vdc	125 Vac, 12 Vdc	125 Vac, 250 Vac	125 Vac, 12 Vdc	12 Vdc
Circuitry	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPNO, SPNC
Max. operating force (gf) at the plunger	100, 200	50, 100, 150, 200, 300	130	150, 203	130	100, 130, 200
Terminations	quick connect	quick connect; wired - 300 mm; special	solder, pcb, pre-wired	solder, pcb, pre-wired	solder, pcb, pre-wired	solder, pcb, pre-wired, clips
Actuators/ levers	pin plunger, roller, straight, long, sim roller	pin plunger, roller, straight, sim roller	pin plunger, straight, sim. roller, formed	pin plunger, straight, roller, sim. roller	pin plunger, sim. roller, formed, straight	pin plunger
Approvals	UL, cUL, ENEC, CQC, RoHS, IEC Ex, ATEX	UL, cUL, ENEC, CQC, RoHS, REACH	UL, cUL, CE, ENEC, CQC, RoHS, REACH	UL, cUL, CE, ENEC, CQC, RoHS, REACH	UL, cUL, CE, ENEC, CQC, RoHS, REACH	UL, cUL, CE, ENEC, CQC, RoHS, REACH
Agency-rated use temp. (°C)	-25 to 85	0 to 55	0 to 55	0 to 70	0 to 55	0 to 55
Contacts	silver alloy, gold-plated	silver nickel, gold-plated	silver, gold-plated silver	silver, gold-plated silver	silver alloy	silver-plated copper alloy
Housing material	PBT polyester	PBT polyester	PBT polyester, polyamide (nylon)	PBT polyester	polyamide (nylon)	PBT Polyester
Dimensions mm H x W x L	15,90 x 10,30 x 33,00	15,90 x 10,30 x 33,00	8,10 x 5,40 x 14,70	9,25 x 6,40 x 19,80	7,4 x 5,4 x 14,7	7,05 x 5,3 x 8,3


* With the exception of the V15W2, all switch families represented by this document require wired designs from the factory to achieve an IP67 rating. Each switch family has terminal versions. While these switches are also sealed, due to their exposed terminals, the formal ingress rating is IP00.

PRODUCT SERIES AND DATASHEETS

Click the product or series to view the Series datasheet.



V15W2



V15W



ZD



ZW



HD



HD1

APPLICATIONS



Presence Detection

Ensures door latching and safe operation



Flow Switch

Enables safe and efficient water usage



Power Switch

Reliable system control for motors, pumps, fans



Operator Controls

Interface control for system auxiliary functions



Float Switch

On/off power to stop overflow conditions

SUPPORTING DOCUMENTATION

Click the document title or icon to view the material.

- Applying Precision Switches
- Sensors and Switches for Medical Applications
- V15W2 Explosion-Proof Basic Switch: Reverse Diagram
- MICRO SWITCH Hazardous Location Approvals Matrix
- Sensors and Switches in Valves and Flowmeters
- Industrial Applications Brochure
- Watertight Switches in Transportation

Honeywell Advanced Sensing Technologies

830 East Arapaho Road
Richardson, TX 75081
800-582-4263
sps.honeywell.com/ast

005000-1-EN | 1 | 05/21
© 2021 Honeywell International Inc. All rights reserved.

Find out more

Honeywell Advanced Sensing Technologies services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit sps.honeywell.com/ast or call: International +815 618 3231; USA/Canada +302 613 4491