

MICRO SWITCH BASIC SWITCH LARGE SWITCH COMPARISON

Ideal for high cost-of-failure applications. Low operating force and differential travel.
Current ratings from 1 A to 25 A. Designed to withstand 100K operations at full load or 10M for mechanical life.

SERIES	BZ	BA	BM	BE	6AS	MT	DT	BS
Type, Market	premium	premium	premium	premium	specialty; tandem switch	designed for power-duty dc loads	Same size as BZ, but DPDT	adjustable differential travel
Use	Switch styles: momentary plunger, manual reset plunger, make-before-break contacts, sequential contacts, double break contacts, split contacts					control circuits to switch high capacity dc systems	simultaneous make/break of two independent circuits	pressure or temp. switch assemblies
Amp rating (A)	1 A, 5 A, 10 A, 15 A	1 A, 15 A, 20 A	22 A	25 A	1 A, 5 A, 10 A, 15 A, 20 A	10 A	10 A	15 A, 20 A
Voltage	125 Vac, 250 Vac, 480 Vac	125 Vac, 250 Vac, 480 Vac	125 Vac, 250 Vac, 480 Vac	125 Vac, 250 Vac, 480 Vac	125 Vac, 250 Vac, 480 Vac	125 Vac/Vdc	125 Vac/Vdc 250 Vac/Vdc	250 Vac, 277 Vac, 480 Vac
Circuitry	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	SPDT, SPNO, SPNC	per each switch	SPDT	DPDT	SPDT, SPNO, SPNC
Operating Force	<1.0 oz to 28 oz	1.0 oz to 35 oz	<1.0 oz to 25 oz	2.5 oz to 25 oz	2 oz to 23 oz	2 oz to 35 oz	2.5 oz to 20 oz	6 oz to 32 oz
Terminations	quick connect, solder, screw, wire harness with connector	quick connect, solder, screw	quick connect, solder, screw	quick connect, solder, screw	quick connect, solder, screw	solder, screw	screw	quick connect, solder, screw
Actuators/ levers	<ul style="list-style-type: none">plunger: pin,high overtravelpanel mountrigid lever: straight, roller, formed adjustableflexible leaf: straight, roller, formed	<ul style="list-style-type: none">plunger: pin,high overtravelpanel mountrigid lever: straight, roller, formedflexible leaf: straight, roller, formed	<ul style="list-style-type: none">plunger: pin,high overtravelpanel mountrigid lever: straight, roller, formed adjustableflexible leaf: straight, roller, formed	<ul style="list-style-type: none">plunger: pin,high overtravelpanel mountrigid lever: straight, roller, formedflexible leaf: straight, roller, formed	common actuator with adjustable synchronicity	<ul style="list-style-type: none">plunger: pin,high overtravelrigid lever: straight, roller, formedflexible leaf: straight, roller, formed	<ul style="list-style-type: none">pin plungerstraight plungerrigid lever: straight, roller	pin plunger (SST)
Approvals	UL, CSA, ENEC, CE, FAA-PMA, MIL-PRF-8805 (varies by model)	UL, CSA, ENEC, CE (varies by model)	UL, CSA, ENEC, CE (varies by model)	UL, CSA	UL, CSA	UL, CSA	UL, CSA, FAA, PMA, MIL-PRF-8805	UL, CSA (most models)
Operating Temp. (°C)	-55 to 85, 121 and 204°C options	-55 to 85, 121 and 204°C options	-55 to 85, 121 and 204°C options	-55 to 85, 121 and 204°C options	-55 to 85	-55 to 82	-55 to 85	-55 to 85
Contacts	gold, silver, silver-copper-nickel	gold, silver, silver cadmium oxide	silver, silver cadmium oxide, silver-tin oxide	silver, silver cadmium oxide	gold, silver, silver cadmium oxide, silver-tin oxide silver-copper-nickel	silver	silver	silver, silver cadmium oxide
Housing material	phenolic: general purpose, heat-resistant, high temperature, mica-filled					phenolic : arc resistant melamine	phenolic: heat-resistant	phenolic: heat-resistant, mica-filled
Dimensions mm H x W x L	25,4 x 17,5 x 49,3	25,4 x 17,5 x 49,3	25,4 x 17,5 x 49,3	25,4 x 17,5 x 49,3	25,4 x 35 x 49,3	25,4 x 17,5 x 49,3	25,4 x 17,5 x 49,3	34,3 x 17,5 x,49.3
Mechanical Life @ 95 % survival	up to 10,000,000 cycles	up to 10,000,000 cycles	up to 10,000,000 cycles	up to 10,000,000 cycles	up to 10,000,000 cycles	up to 500K operations	up to 20,000,000 cycles	Up to 10,000,000 operations

Honeywell Sensing and Internet of Things

830 East Arapaho Road
Richardson, TX 75081
800-582-4263
www.honeywell.com

004999-1-EN | 1 | 01/21
© 2021 Honeywell International Inc. All rights reserved.

Find out more


Honeywell Sensing and Internet of Things services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit sensing.honeywell.com or call: International +815 618 3231; USA/Canada +302 613 4491



Our Large Basics have offered the **tightest & most precise characteristic specifications** for almost a century.



MICRO SWITCH Large Basics are **rugged, strong,** and built to outlast the toughest applications



These switches thrive in high cost-of-failure applications with **MIL** and **FAA-PMA approvals**.

PRODUCT SERIES AND DATASHEETS

Click the product or series to view the Series datasheet.



BZ



BA



BM



BE




6AS



MT



DT



BS

APPLICATIONS



Power Switch

Reliable system control for motors, pumps, fans



Presence Detection

Ensures door latching and safe operation



Pressure Switch

Detection and warning of high pressure or over pressure events



Flow Switch

Enables safe and efficient water usage



Float Switch

On/off power to stop overflow conditions

SUPPORTING DOCUMENTATION

Click the document title or icon to view the material.



Applying Precision Switches



Sensors and Switches for Medical Applications



Industrial Applications Brochure



Sensors and Switches in Valves and Flow Meters



Case Study: BZ Switches

Honeywell