

MICRO SWITCH PK 8119 O

HEAVY DUTY LS LIMIT SWITCH WITH GOLD PLATED CONTACTS

— CAUTION —

This switch is designed to carry electrical loads given under Electrical Ratings **A** and **B** (see chart). However, if the switch is used at the higher current levels (Electrical Rating **A**), the gold plating will burn off the contacts. The switch will then no longer be reliable for low energy loads (Electrical Rating **B**).

ELECTRICAL RATINGS

Circuits on any one pole must be same polarity.

10 amps. Continuous Carry

PILOT DUTY 600 VAC - 720 VA 240 VDC - 30 WATTS							
	AC VOLTS	CURRENT 0.35 POWER FACTOR		DC VOLTS	MAKE AND BREAK AMPS		
		AMPS			INDUCTIVE	RESISTIVE	
		MAKE	BREAK				
A*	120	60	6.0	A	120	0.25	0.8
	240	30	3.0		240	0.15	0.4
	480	15	1.5				
	600	12	1.1				
ELECTRONIC DUTY RATED							
B =	Electronic Duty - 5 VAC or VDC .01 amp (Recom. min. load)						

* For switches with indicator light,
use only at voltage stated for
indicator light.

MICRO SWITCH

FREEPORT, ILLINOIS 61032

A DIVISION OF HONEYWELL

IN CANADA: 740 Ellesmere Road, Scarborough, Ontario. INTERNATIONAL: Sales and service offices in all principal cities of the world.

PK8119O 1276 PRINTED IN USA