



| | |
|------------|-------------------|
| 2116-2400K | 2,400,000 |
| 2116-1200K | 1,200,000 |
| MODEL | CAPACITY-IN. LBS. |

OUTPUT ~ 2.0MV/VOLT MIN. NOMINAL

| DET. NO. | PART NO. | DESCRIPTION | REQ'D |
|-------------------------------|-------------------------------------|---|----------------------|
| | | OUTSIDE DIMENSIONS - FLANGED REACTION TORQUE SENSOR | |
| SCALE: HALF | DRAWN BY: D.A. ANDREWS | REF. DRWG: C-12802 | MAT'L: |
| DATE: 9-10-65 | CHK'D BY: | MODEL: 2116 | JOB NO: |
| UNLESS OTHERWISE SPECIFIED: | | | |
| TOLERANCE ON FRACTIONS ± 1/64 | TOLERANCE ON DRILLED HOLES ± .007 | REMOVE ALL BURRS & SHARP EDGES | |
| TWO PLACE DECIMALS ± .010 | DIMENSION LIMITS HELD AFTER PLATING | | |
| THREE PLACE DECIMALS ± .005 | SURFACE FINISH 125.7 | | |
| LEBOW ASSOCIATES, INC. | | | DRAWING NO. C-2116-D |
| OAK PARK, MICHIGAN | | | |
| SYN. | REVISION | DATE | |