



SPECIFICATIONS

AVAILABLE RANGES: SEE TABLE
 EXCITATION: 10 VDC
 OUTPUT (nom): 5 mV/V ©
 NONLINEARITY (max): ± .20% F.S.
 HYSTERESIS (max): ± .20% F.S. ©
 COMPENSATED TEMPERATURE: -65°F TO 250°F
 TEMPERATURE EFFECT:
 ZERO (max): .020% F.S./°F ©
 SPAN (max): .020% Rdg./°F ©
 WETTED MATERIAL: 17-4 PH SS

UNAMP#1,4-COND CABLE

COLOR	DESIGNATION
RED	(+)EXCITATION
BLACK	(-)EXCITATION
GREEN	(-)OUTPUT
WHITE	(+)OUTPUT

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS	C 8/15/2005	05-284: SPECIFICATIONS UPDATED	MILLER	BDR	OSS	
	B 1/26/05	05-035: 5 FT TFL JACKET CABLE WAS 6-PIN CONNECTOR	MILLER	BDR	OSS	
	REV	DESCRIPTION	REV BY	CHK BY	APV BY	
DRW: MILLER 12/28/2004	CHK: RICHARDS 01/07/2005	MFG:	ENG: OSMITH 01/03/05			
REV A HIST 05-007	DO NOT SCALE .X ±.2 .XX ±.02 .XXX ±.010	Honeywell				HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing
OUTLINE DRAWING, Ø1 1/8" DIFF PRESSURE 7/16-20 MALE, CABLE						
CODE IDENT NO. 51518		DOCUMENT NUMBER				
SHEET 1 OF 1		SIZE A		000-B135-00		

-02			
060-B135-01	5 PSID	250	250
PART NUMBER	RANGE	LINE PRESSURE	SIDE TO SIDE PRESSURE