



SPECIFICATIONS:

RATED CAPACITY — 600,000 IN LBS & 750,000 IN LBS.
 OUTPUT @ RATED CAP — 2.0 MV/V NOM
 BRIDGE RESISTANCE — 350 Ω

1 3/4" DIA - 8 HOLES EQUALLY SPACED
 BOTH FLANGES

REV. NO.	PART NO.	DESCRIPTION	REVISION
OUTSIDE DIMENSIONS FLANGED REACTION TORQUE SENSOR			
SCALE: FULL		DATE: 8-6-65	DRAWN BY: D.A. ANDREWS
TOLERANCE ON FRACTIONS: 1/16"		TOLERANCE ON DRILLED HOLES: ±.005"	
TWO PLACE DECIMALS: ±.010"		REMOVE ALL BURRS & SHARP EDGES	
THREE PLACE DECIMALS: ±.005"		DIMENSION LINES WELD AFTER PLATING	
ANGLES: ±.1°		SURFACE FINISH: 125	
UNLESS OTHERWISE SPECIFIED:		DRAWING NO.:	
A ADDED		2285	
REV. NO.		DATE	
		LEBOW ASSOCIATES, INC.	
		D-2115-D	

SCANNED
 3/11/2018 10:07

REF: D-12774