

AMP(NS),2-COND,CBL  
COLOR DESIGNATION  
 RED (+)SUPPLY  
 BLACK (+)OUTPUT

001-0704-00

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS			-	INITIAL RELEASE TO PRODUCTION			-	-	-	
AUTOCAD			REV	DESCRIPTION			REV BY	CHK BY	APV BY	
REV HIST			DRW: MLF	CHK: VICARS	MFG: -	ENG: VICARS				
			04/15/1996	04/18/1996	XX/XX/XX	04/18/1996				
DATABASE VERIFIED:			DIETRICK	10/04/2004	<b>Honeywell</b>				HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 <a href="http://www.honeywell.com/sensing">www.honeywell.com/sensing</a>	
PLOT FILE VERIFIED:			DIETRICK	10/04/2004	EXTERNAL WIRING CODE AMP(NS),2-COND,CBL					
CATALOG VERIFIED:			N/A	N/A	CODE IDENT NO. <b>51518</b>		DOCUMENT NUMBER			
CATALOG REFERENCE:					SHEET 1 OF 1	SIZE A	001-0704-00			