

AMP(NS),2-COND,CBL
COLOR DESIGNATION
 RED (+)SUPPLY
 BLACK (+)OUTPUT

001-0704-00

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS			-	INITIAL RELEASE TO PRODUCTION		-	-	-	
			-						
REV	DESCRIPTION			REV BY	CHK BY	APV BY			
AUTOCAD			DRW: MLF 04/15/1996	CHK: VICARS 04/18/1996	MFG: - XX/XX/XX	ENG: VICARS 04/18/1996			
REV HIST			Honeywell						HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing
DATABASE VERIFIED:	DIETRICK	10/04/2004	EXTERNAL WIRING CODE						
PLOT FILE VERIFIED:	DIETRICK	10/04/2004	AMP(NS),2-COND,CBL						
CATALOG VERIFIED:	N/A	N/A	CODE IDENT NO. 51518			DOCUMENT NUMBER			
CATALOG REFERENCE:			SHEET 1 OF 1	SIZE A	001-0704-00				