



WIRING CODE

6 COND. SUBMERSIBLE, 4-20 mA, 3 WIRE AMP

COLOR	DESIGNATION
RED	(+)SUPPLY (+22-32 VDC)
BROWN	OUTPUT COMMON
GREEN	SUPPLY RETURN
ORANGE	(+)OUTPUT (4-20 mA)
BLUE	SHUNT CAL 1
YELLOW	SHUNT CAL 2

NOTE : INTERCONNECTING SHUNT CAL 1 AND SHUNT CAL 2 PROVIDES 80% FULL-SCALE OUTPUT FOR QUICK CALIBRATION

SPECIFICATIONS

- 1.AVAILABLE RANGE : 0-25" THRU 0-1000"H2O OR 0-1 THRU 0-50 PSIG
- 2.ACCURACY : +/- 0.1%
- 3.OUTPUT : CURRENT (3 WIRE) AMPLIFIER
- 4.SUPPLY : 22 TO 32 VDC
- 5.COMP. TEMP : 60-160 DEG.F
- 6.COMP. TEMP ERROR
 ZERO : +/-0.0025 % fs/DEG.F
 SPAN : +/-0.0025 % fs/DEG.F
- 7.WETTED MATERIAL : 17-4 PH SS

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS				A	INITIAL RELEASE TO PRODUCTION	BNK		
AUTOCAD				REV	DESCRIPTION	REV BY	CHK BY	APV BY
REV HIST				DRW:	BNK	CHK:	MFG:	ENG:
				08/15/2008		-	xx/xx/xx	xx/xx/xx
				DO NOT SCALE				
				.X	HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing			
				±.2	MODEL LL-V STD.PRODUCT			
				.XX	5 THRU 100 PSI			
				±.02	CODE IDENT NO.		DOCUMENT NUMBER	
				.XXX	51518		000-1927-00	
				±.010	SHEET	SIZE		
					1 OF 1	A		