

Application Note

TruStability™ Board Mount Pressure Sensors

RSC Series—High Resolution, High Accuracy, Compensated/Amplified

±1.6 mbar to ±10 bar | ±160 Pa to ±1 MPa | ±0.5 inH₂O to ±150 psi

24-bit Digital SPI-Compatible Output

Background

The RSC Series is a piezoresistive silicon pressure sensor offering a digital output for reading pressure over the specified full scale pressure span and temperature range. It is calibrated and temperature compensated for sensor offset, sensitivity, temperature effects, and non-linearity using a 24-bit analog-to-digital converter with integrated EEPROM. Pressure data may be acquired at rates between 20 and 2000 samples per second over an SPI interface. It is intended for use with non-corrosive, non-ionic gases, such as air and other dry gases, designed and manufactured according to ISO 9001 standards, and is REACH and RoHS compliant.

Solutions

MEDICAL

Spirometers

- Use in application: Designed to measure the pressure drop in a flow tube as the patient is inhaling and exhaling. This pressure measurement is used to calculate the volume of air in a patient's lung.
- Benefits to customer:
 - Extremely high accuracy at a zero and low flow condition
 - High resolution allows measurement of extremely low flows with a minimum pressure drop
 - Small size helps integration into hand-held/mobile devices
 - Cost effective solution for high volume applications

Ventilators

- Use in application: Designed to measure the pressure as a patient is inhaling and exhaling. A pressure measurement is used to measure the precise moment when the patient changes from inhalation and exhalation. Another pressure measurement is used to calculate the volume of the lungs to determine how much air to supply.
- Benefits to customer:
 - Extremely high accuracy and resolution at a zero and low flow condition enhances the accuracy of the trigger sensor and may allow the same pressure sensor to be used in both pediatric and general ventilators

- Small size allows the sensor to be moved closer to the patient, which improves accuracy
- Cost-effective solution for high volume applications

INDUSTRIAL

VAV Controls

- Use in application: Designed to measure the pressure drop across a restrictor in an air duct. This measurement is used to calculate the airflow in the duct.
- Benefits to customer:
 - Extremely high accuracy at a zero and low flow condition
 - High resolution allows measurement of extremely low flows with a minimum pressure drop
 - Cost-effective solution for high volume applications
 - Excellent long term stability minimizes re-zeroing
 - Tight Total Error Band minimizes errors with temperature changes in the buildings

Altitude Measurement for Drones, Aerial Systems and Aircraft

- Use in application: Designed to measure barometric pressure, which is used to measure altitude.
- Benefits to customer:
 - High resolution allows accurate measurement of altitudes
 - Tight Total Error Band minimizes errors due to change in air temperature
 - Small size and low mass allows for potential use in critical small drone applications
 - Cost-effective solution for high volume applications


Application Note

TruStability™ Board Mount Pressure Sensors

RSC Series—High Resolution, High Accuracy, Compensated/Amplified

±1.6 mbar to ±10 bar | ±160 Pa to ±1 MPa | ±0.5 inH₂O to ±150 psi

24-bit Digital SPI-Compatible Output

RSC Series	Features
	<ul style="list-style-type: none">• Pressure range: ±1.6 mbar to ±10 bar ±160 Pa to ±1 MPa ±0.5 inH₂O to ±150 psi; absolute range 1 bar to 8 bar 15 psi to 150 psi• Pressure types: Absolute: internal vacuum reference and an output value proportional to absolute pressure; Gage: referenced to atmospheric pressure and provide an output proportional to pressure variations from atmosphere; Differential: allows measurement of pressure between the two pressure ports• Total Error Band: As low as ±0.25 %FSS depending on pressure range (after auto zero)• Accuracy: ±0.1 %FSS BFSL (Full Scale Span Best Fit Straight Line)• Compensated temperature range: -40 °C to 85 °C [-40 °F to 185 °F]• Power consumption: Less than 10 mW, typ.• Size: Miniature 10 mm x 12,5 mm [0.39 in x 0.49 in] package• Output: 24-bit digital SPI-compatible• Meets IPC/JEDEC J-STD-020D.1 Moisture Sensitivity Level 1 requirements

Find out more

To learn more about Honeywell Safety and Productivity Solutions' products, call **+1-815-235-6847** or **1-800-537-6945**, visit sensing.honeywell.com, or e-mail inquiries to info.sc@honeywell.com

Warranty/Remedy. Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship during the applicable warranty period. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items that Honeywell, in its sole discretion, finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While Honeywell may provide application assistance personally, through our literature and the Honeywell web site, it is buyer's sole responsibility to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this writing. However, Honeywell assumes no responsibility for its use.

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
honeywell.com

008312-2-EN IL50
October 2016
Copyright © 2016 Honeywell International Inc. All rights reserved.

