

**AMP#21,6-COND,CBL,SMS,SHN**

<b>COLOR</b>	<b>DESIGNATION</b>
<b>RED</b>	<b>(+)SUPPLY</b>
<b>BROWN</b>	<b>(-)OUTPUT</b>
<b>GREEN</b>	<b>SUPPLY RETURN</b>
<b>ORANGE</b>	<b>(+)OUTPUT</b>
<b>BLUE</b>	<b>SHUNT CAL 1</b>
<b>YELLOW</b>	<b>SHUNT CAL 2</b>

001-0333-21

# AMP#36, 3-COND, 4-PIN, DIN, GND

---

PIN

DESIGNATION

---

1	(+)SUPPLY
2	(+)OUTPUT
3	NO CONNECTION
$\perp$	CASE GROUND

001-0333-36

# AMP#43, 3-COND, 6-PIN, GND

---

## PIN DESIGNATION

---

A	(+)SUPPLY
B	N/C
C	N/C
D	(+)OUTPUT
E	CASE GROUND
F	N/C

001-0333-43

# AMP(RS-485),7-COND,8-PIN

PIN	DESIGNATION
A	(+)RS485 TxD
B	(+)OUTPUT
C	OUTPUT RETURN
D	N/C
E	SUPPLY COMMON
F	(+)SUPPLY
G	(-)RS485 RxD
H	GROUND, RS485

001-1155-02