

UNAMP,4-COND,5-COND,6-COND,4-PIN,5-PIN,6-PIN

4-PIN		5-PIN		6-PIN	
PIN	FUNCTION	PIN	FUNCTION	PIN	FUNCTION
A	(+)EXC.	A	(+)EXC.	A	(+)EXC.
B	(+)SIG.	B	(+)SIG.	B	(+)SIG.
C	(-)SIG.	C	(-)SIG.	C	(-)SIG.
D	(-)EXC.	D	(-)EXC./	D	(-)EXC.
			TEDS GND	E	TEDS GND
		E	TEDS DATA	F	TEDS DATA

\* USE TEDS CONNECTIONS WHEN REQUIRED

001-LWR-100

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS		A 7/18/2006	PIN E WAS "TEDS DATA", PIN F WAS "TEDS GND" FOR 6 PIN CONN	MGJ	RJG	MGF	
AUTOCAD		-	INITIAL RELEASE TO PRODUCTION				
REV	DESCRIPTION	REV	BY	CHK	BY	APV	
DRW: DURKIN	CHK: VICARS	MFG: -	ENG: OSMITH				
	12/15/05	05/09/2006	05/03/2006				
REV HIST	DO NOT SCALE	<b>Honeywell</b>				HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing	
PCB DWG & REV:	.X						
-	±.1	EXTERNAL WIRING CODE		UNAMP, 5 & 6-COND, 5 & 6-PIN		100	
CHECKOUT PROCED:	.XX	CODE IDENT NO.		DOCUMENT NUMBER		100	
-	±.01	51518		001-LWR-100			
SCHEMATIC:	.XXX	SHEET	SIZE				
-	±.005	1 OF 1	A				
LAYOUT:	±1/2"						
-							
DRILL PATTERN:							
-							