



SPECIFICATIONS:  
 AVAILABLE RANGE: 0 to 10 THRU 0 to 1500 PSIA  
 OUTPUT: 3 mv/v  
 EXCITATION: 10 VDC  
 TEMPERATURE COMPENSATED: 60 to 160 DEF.F.  
 OPERATING TEMPERATURE: -100 to 325 DEG.F.  
 OVERALL ACCURACY:  
 MODEL TJE = +/- 0.1% F.S.  
 Z = +/- 0.25% F.S.  
 A-5 = +/- 0.5% F.S.  
 WETTED MATERIAL: 17-4 PH S.S.

WIRING CODE  
 UNAMP (S) 6-PIN, 6-COND  
 PIN A & B = (+) EXCITATION  
 C & D = (-) EXCITATION  
 E = (-) OUTPUT  
 F = (+) OUTPUT

OUTLINE DWG. FOR P/N 060-0713-XX

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS					-	-
REV	DESCRIPTION	REV BY	CHK BY	APV BY		
DRW: DILLON 09/11/1979	CHK: FRESCO 11/05/2003	MFG: FRESCO 12/05/2003	ENG: RICHARDS 12/02/2003			
AUTOCAD						
REV HIST	DO NOT SCALE	<p>HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing</p>				
	.X ±.2					
	.XX ±.02					
	.XXX ±.010					
		PRESSURE TRANSDUCER 1.5" DIA, ABSOLUTE				
		CODE IDENT NO. 51518	DOCUMENT NUMBER			
		SHEET 1 OF 1	SIZE A	000-0641-00		