


UNAMPLIFIED
5-COND, 5-PIN

PIN	DESIGNATION
A	(-)OUTPUT
B	(+)EXCITATION
C	(-)EXCITATION/ TEDS GND
D	(+)OUTPUT
E	TEDS DATA

001-LWR-136

IF THIS IS A PAPER COPY IT IS UNCONTROLLED. VERIFY REVISION BEFORE USE.

PROPRIETARY RIGHTS NOTICE: THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS IN INCHES. INTERPRET PER ASME Y14.100-2000 OTHER HONEYWELL STDS MAY APPLY. ALL FILLETS & CORNERS .005R MAX DEBURR & BREAK SHARP CORNERS		-		INITIAL RELEASE TO PRODUCTION		-	-	-
		REV	DESCRIPTION		REV BY	CHK BY	APV BY	
AUTOCAD		DRW: FOWLER	CHK: -	MFG: -	ENG: OSMITH			
		05/19/2006	-	-	05/22/2006			
REV HIST	DO NOT SCALE	 HONEYWELL SENSOTEC 2080 ARLINGATE LANE COLUMBUS, OHIO 43228 www.honeywell.com/sensing						
	.X							
	.XX							
	.XXX							
	±.2	EXTERNAL WIRING CODE						
	±.02	SPECIAL, 5-COND, 5-PIN						
	±.010	CODE IDENT NO. 51518		DOCUMENT NUMBER				
		SHEET 1 OF 1	SIZE A	001-LWR-136				